

primo

Model Code E8941

date of issue 16-09-22 revision 00
revision of 13-10-22 (the present replaces any previous versions)



Designer: centro studi interno

Structure: pinewood, multilayer and plywood covered with polyurethane foam.

Spring system: elastic webbing

Seat Padding: seat cushions in ecological polyurethane foam, covered with 100% polyester padding

Back Padding: fiber (synthetic fiberfill)

Arm Interior: ecological polyurethane foam, covered with 100% polyester padding

Removability: not available

Sewing: leather coverings feasible with contrast stitching in the colors available; cuts and sewing vary on microfibre (or fabric) coverings.

Mechanisms: electric recliner versions available with electrically powered recliner metal mechanism operated by a button panel positioned on armrests outer sides. The depth of the open recliner is 154 cm.

Optional feet: black PVC, h 5 cm.

Density of seat and back kg/cbm (±5%) ⁽¹⁾

Markets	Seat	Back
I	30 Medium	
D - NL - CH		
USA - California	30 soft	
GB	37 fire retardant	
Others		

Note: when no values/contents are specified in the chart, please refer to 'Others' field/area.

⁽¹⁾Density: volume mass apparently determined on materials without any kind of covers and according to the UNI EN ISO 845 regulations. Indicated values refer to production averages; the Company reserves the right, if needed, to make changes to the declared technical characteristics. Before use, it is advisable to look at the SAFETY INFORMATION TECHNIQUE for info regarding use and protection of people and of the environment, in compliance with existing EEC regulations.

Coverings

	suggested	not suggested	not possible
thick leathers	✓		
thin elastic leathers	✓		
natural leathers	✓		
fabric*	✓		
microfibre*	✓		
leather + split	✓		
DeLuxe			✓
multi colour**			✓
multi-category**			✓
multi covering**			✓

Please note: for not removable models, only one colour fabric covers are available.

* fabrics and microfibers are not available for the U.K. market

Components / Optional vers.



Feet



PVC H6



Ottoman



With the reservation of carrying for production purposes and without advanced notices modifications on the materials, coverings and dimensions of the product as indicated in the relevant specification. The given dimensions and volume are of indicative value being subject to the production process tolerances. For normal use, the following maximum loads are recommended: Armchairs max. 120 kg, 2-seat sofas max. 200 kg (2x100 kg), 3-seat sofas max. 240 kg (3x80 kg). Use with loads exceeding the indicated values may cause the sofa/armchair or its components to break.



↑ fold following the dotted line ↑

primo



L Length - H Height - D Depth - SH Seat Height - SD Seat Depth
Dimensions refer to maximum sizes of the version with closed mechanism (where available).

dimensions	L 110 H100 D95 SH47 SD53	L 110 H100 D95 SH47 SD53	L 170 H100 D95 SH47 SD53	L 170 H100 D95 SH47 SD53	L 205 H100 D95 SH47 SD53
version code	100	161	200	408	300
Description	chair	chair with elec.recl.	2 seater	2str rg/lf rec.el.	3 seater

L 205 H100 D95 SH47 SD53
T09
3 seat.2cush.2 rhf/lhf el.rec.

↓ fold following the dotted line ↓

